

CS Hyde Company

39655 N IL Route 83
Lake Villa, IL 60046
Ph. 847-395-0325 Fax 847-395-0334
sales@cshyde.com / www.cshyde.com



PRODUCT INFORMATION

43-F-BLK
Black HDPE
Polyethylene Film

PRODUCT DESCRIPTION

Black High Density Polyethylene Film is offered in .015" or .030" thick. HDPE is moisture resistant and has superior strength when compared with LDPE. It has more rigidity than LDPE and offers better heat resistance. Uses: pipe, shipping pallets, truck bed liners.

HDPE is sold by the foot and is 47" wide. Rolls are 100 Foot long

TECHNICAL DATA

PROPERTIES	ASTM	UNITS	DATA
Specific Gravity	D-792	g/cc	.952 - .965
Melt Flow @ 190°C / 2.16kg	D-1238	g/10 min	.3 - .45
Tensile Strength @ Yield	D-638	Psi	3,800 - 4,800
Flextural Modulus	D-790	Psi	145,000 - 225,000

Note: Tests, claims representations and descriptions regarding flammability are based on standard laboratory tests and, as such, may not be reliable for determining, evaluating, predicting or describing the flammability of burning characteristics under actual fire conditions, whether used alone or in combination with other products. Accordingly, each potential user should make an individual determination whether the flammability or burning characteristics of the product are suitable for the purpose intended by the user.